Argentine Polypropylene Plant Stays Innovative with Advanced Process Control Software

Tighter process control has given the facility greater ability to minimize deviations in production conditions and improve model building capabilities.





Petroquimica Cuyo pioneered the production of polypropylene in Argentina and special polyolefins in Latin America. They continue as a leader in innovation, quality and variety of products fully committed to their clients, industrial safety and environment.

In 1995, it became the first Argentine company, and the first petrochemical company in the Americas, to obtain ISO 14001 certification in Environmental Management.

The following year, the company was accredited under the ISO 9001 standard, which encompasses design, development, production, sales, customer service and aftermarket service.

In 1998, working in Safety and Health Management, under the guidance of BS8800, it was certified in the equivalent IRAM 3800 standard.

Given this emphasis on innovation and efficiency, Petroquimica Cuyo sought to improve productivity at its Mendoza, Argentina, facility which has a capacity of 120,000 tons/year, producing homopolymers, impact copolymers, random copolymers, terpolymers, and special polyolefins.


The strategy was to establish optimum regulatory control at the plant, which is essential for providing consistent, safe process operations and securing economic benefits.

Petroquimica Cuyo determined that the regulatory control it was seeking could be achieved through advanced tuning software. Several software packages from different vendors were considered, and the decision was made to select the ABB Loop Performance Manager (LPM) for the Mendoza plant.

There were a number of reasons for this preference, including the ability to use a single user interface for all the PID tuning processes such as data collection, modeling, tuning and simulation. LPM has online data collection through OPC, which supports open connectivity via open standards.

LPM has a very simple and powerful Model Identification and Evaluation package that is oriented to different users profiles. Additionally, LPM can support a wide variety of commercial PID controllers, as well as various configuration options for PID control algorithms.

LPM features a very flexible and complete set of tuning methods, plus automatic tuning and analysis for Feed Forward (FF) and Cascade Control Loops.



Figures 1 and 2 show different steps of the tuning process using LPM. Control engineers appreciated the full functionality of the ABB loop tuning software, especially the ability to create process models. The control engineers found LPM very useful. Consider the LPM application on a distillation column and heat exchanger. Single loops were tuned primarily with the Lambda method for simple loops, and Dominant Pole Placement for complex ones.

Cascade loops were treated in a special manner by LPM, considering the inner loop when tuning the outer loop.

Feed Forward controllers were implemented for some pump-around flows, visibly reducing the variation of the column level loops.

In cases where gain scheduling was needed due to non-linear behavior, such as heat exchange temperature control at different operating points, the possibility of LPM to create process models and tuning was very helpful.

The engineers found the effectiveness of these techniques useful for important reductions in the standard deviations at the regulatory level.

Among the advantages the customer identified with LPM were the capability to analyze the current tuning of a PID based on the built process model, using the manual tuning option, and the fact that the PID parameters were given in the controller's own form of implementation, that is, no conversion was needed.

BENEFITS:

- Convenient, single interface for all PID tuning processes is provided
- Problem-solving is simplified with LPM's ability to create process models
- Comprehensive set of tuning methods are provided with features such as automation tuning, depending on application

Also mentioned were the possibility to specify the control behavior using one or more sliders defining the trade-off between the robustness and performance for a chosen tuning method, as well as the frequency domain analysis parameters.

Petroquimica Cuyo found LPM the software they were looking for. Besides its usefulness for loop tuning activities, it can be used to gain valuable process insight through its model building capabilities. It is helping the Mendoza facility operate at peak efficiency and meet market demand.






Figure 2. Loop Tuning and Evaluation with LPM



Figures 3 and 4 show different trends and standard deviations of the output temperature of a heat exchanger before and after the PID controllers were tuned with the ABB LPM.

Figure 3. Non-linear Application Tuning using LPM: performance before tuning activity





ABB

Process Automation Division

Västerås, Sweden Phone: +46 (0) 21 32 50 00 Fax: +46 (0) 21 13 78 45 www.abb.com/controlsystems email: processautomation@se.abb.com

ABB

Process Automation Division Singapore

Phone: +65 6776 5711 Fax: +65 6778 0222 www.abb.com/controlsystems email: processautomation@sg.abb.com

3BUS094495 en US Creative Services 1221

ABB

Process Automation Division Wickliffe, Ohio, USA Phone: +1 440 585 8500 Fax: +1 440 585 8756 www.abb.com/controlsystems email: industrialitsolutions@us.abb.com

ABB

Process Automation Division Mannheim, Germany

Phone: +49 (0) 1805 26 67 76 Fax: +49 (0) 1805 77 63 29 www.abb.de/controlsystems email: marketing.control-products@de.abb.com

© Copyright 2007 ABB. All rights reserved. Specifications subject to change without notice. Pictures, schematics, and other graphics contained herein are published for illustration purposes only and do not represent product configurations or functionality. User documentation accompanying the product is the exclusive source for functionality descriptions. The Industrial^{IT} wordmark, Aspect Objects, and all above-mentioned names in the form XXXXXX^{IT} are registered or pending trademarks of ABB. All rights to other trademarks reside with their respective owners.